

## Pneumatic Plier Type 195/25-526

The BeA Pneumatic Plier 195/25-526 guarantees secure of a variety of materials from 5 to 45 mm. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The plier drives staples type 195 in the length of 15 to 25 mm.



### Popular applications:

Clinching of: cardboard, bag headers, poster coverings, closing of buckets

Length: 324 mm  
Width: 57 mm  
Height: 359 mm

### Technical data

|   |                               |
|---|-------------------------------|
| Type description:                                 | <b>195/25-526</b><br>Standard |
| Article code:                                     | 12000150                      |
| Magazine type :                                   | Top loader                    |
| Fastener type:                                    | Type 195                      |
| Magazine capacity:                                | 135                           |
| Fasteners per strip:                              | 2 x 63                        |
| Operating pressure:                               | 5 – 8 bar                     |
| Max. operating pressure:                          | 8 bar                         |
| Air consumption/operation:                        | 0.83 liters / 6 bar           |
| Inner hose diameter:                              | Ø 9 mm LW recommended         |
| Emission sound pressure level at the workstation: | L pA, 1s, d = 76 dB           |
| Single-shot emission sound pressure level:        | L WA, 1 s,d = 83 dB           |
| Weight:   | 1.74 kg                       |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

**Extras supplied with the plier:** Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)


## Pneumatic Plier Type 195/25-526



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: +49 (0) 4102 78-0  
Fax: +49 (0) 4102 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG

### Staples type 195



| Description | L = Length<br>mm |
|-------------|------------------|
| 195/15 NK   | 15               |
| 195/18 NK   | 18               |
| 195/21 NK   | 21               |
| 195/25 NK   | 25               |

#### Explanations:

|                                    |                                |  |                      |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel              | BK = bright steel              | LM = aluminium                         | HZ = resin coated    |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard       | MS = brass                     | RF = rust resistant, material 1.4301   | SA = step cut        |