



For wire collated
BDC nails



BeA Pneumatic Nailer 570 DC

For nails: BDC 2.1 - 2.5 mm in the lengths of 25 - 57 mm

- Extremely powerful and sturdy
- 360° adjustable exhaust
- Integrated sound absorption
- Ergonomic handgrip, operator friendly
- Adjustable coil nail support (metal)
- Dust and dirt protection
- Contact actuation

Applications

Finishings, siding / cladding, sheathing, sub flooring,
pallets, boxes and cases




BeA 570 DC

Technical Data



Article code	12100456
EAN code	4045759047452
Magazine type	Top loader
Weight	2.7 kg
Dimensions in mm	L 302, H 285, B 132
Safety system	Contact actuation
Fastener type	Type BDC
Magazine capacity	max. 350 nails
Operating pressure	5 - 8 bar
Max operating pressure	8 bar
Air consumption/operation	1.6 litre / 6 bar
Inner hose diameter	9 mm recommended
Emission sound pressure level at the workstation	$L_{pA, 1s, d} = 93.7$ dB
Single shot emission sound pressure level	$L_{WA, 1s, d} = 99.7$ dB
Vibration level as per ISO 8662-11 is	3.73 m/s^2 .
Accessories	Operating instructions, spare parts list, service instructions, allen wrench, lubrication oil, safety glasses

Coil nails BDC



BDC: 25 - 57 mm

BDC nails = wire welded coil nails	
Width	2.1 - 2.5 mm
Length	25 - 57 mm
Material	BK = steel, bright NK = steel, electro galvanized RF = stainless steel, comparable to material 1.4301 NR = stainless steel, comparable to material 1.4401 FV = steel, hot dipped galvanized
Surface properties	Smooth Ring shank Screw shank
Nail heads	Flat head Dome head Pozi head Torx head

Further types on request, nails conforming to DIN1052 and to EN 14592 (Eurocode 5)

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Further Information:
Phone: +49 (0) 41 02 78 - 283
Fax +49 (0) 41 02 78 - 275
Email: info@bea-group.com
www.Bea-Group.com

BeA is a member of the following trade associations:

