



For wire collated
BDC nails



BeA Pneumatic Nailer 730 DC

For nails: BDC 2.3 - 2.9 mm in the lengths of 45 - 70 mm

- Extremely powerful and sturdy
- Ergonomic handgrip, operator friendly
- Dust and dirt protection
- Reinforced nose piece
- Adjustable coil nail support (metal)
- Thread for mounting
- Tool body protection

Applications

Finishings, siding / cladding, sheathing, sub flooring,
pallets, boxes and cases



BeA 730 DC

Technical Data




Article code	12100490
EAN code	
Magazine type	Top loader
Weight	3.8 kg
Dimensions in mm	L 307, H 317, B 131
Safety system	Contact actuation
Fastener type	Type BDC
Magazine capacity	max. 250 - 300 nails
Operating pressure	5 - 8 bar
Max operating pressure	8 bar
Air consumption/operation	2.75 litre / 6 bar
Inner hose diameter	9 mm recommended
Emission sound pressure level at the workstation	L _{pA, 1s, d} = 102.8 dB
Single shot emission sound pressure level	L _{WA, 1s, d} = 107.8 dB
Vibration level as per ISO 8662-11 is	2.68 m/s ² .
Accessories	Sturdy case, Operating instructions, spare parts list, service instructions, allen wrench, oil, safety glasses

Coil nails BDC

BDC nails = wire welded coil nails

Width	2.3 - 2.9 mm
Length	45 - 70 mm



BDC: 45 - 70 mm

Material	BK = steel, bright
	NK = steel, electro galvanized
	RF = stainless steel, comparable to material 1.4301
	NR = stainless steel, comparable to material 1.4401
	FV = steel, hot dipped galvanized
Surface properties	Smooth
	Ring shank
	Screw shank
Nail heads	Flat head
	Dome head
	Pozi head
	Torx head

Further types on request, nails conforming to DIN1052 and to EN 14592 (Eurocode 5)

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Further Information:
Phone: +49 (0) 41 02 78 - 444
Fax +49 (0) 41 02 78 - 270
Email: info@bea-group.com
www.Bea-Group.com

BeA is a member of the following trade associations:

