

## Pneumatic Bradder Type SK 325-521

The small and lightweight bradder SK 325-521 drives brads type SK 300 Ø 1,2 mm from 14 to 25 mm.

The special formed nose allows to work at narrow working places.

This is a versatile tool for industry and the craftsman.



### Popular applications:

Attachment of decorative sealing strips, ornaments, rosettes, glazing strips, trim, moulding, chair rails etc.

Length: 230 mm  
Width: 45 mm  
Height: 181 mm

### Technical data

Type description:	<b>SK 325-521 Standard</b>
Article code:	12000430
Magazine type :	Side loader
Safety:	-
Fastener type:	Brads Type SK 300
Magazine capacity:	80
Fasteners per strip:	2 x 40
Operating pressure:	5 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0.45litre / 6 bar
Inner hose diameter:	Ø 9 mm LW empfohlen
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB
Weight:	1.28 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the bradder:

Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories:

Article code	Description
14403330	Remote valve, complete
14403535	Mounting flange


All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

## Pneumatic Bradder Type SK 325-521

### Brads type SK 300



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: +49 (0) 4102 78-0  
Fax: +49 (0) 4102 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG

Description	L = Length mm
SK 314 NK	14
SK 316 NK	16
SK 319 NK	19
SK 322 NK	22
SK 325 NK	25

The SK 200 finish nail heads are coloured brown (standard).  
Other colours are also available on request.

#### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut