

Pneumatic Tacker

71/16-421

This light but powerful tacker of the BeA 420 series takes staples type 71 in lengths from 5/32" to 5/8". The low air consumption, long service life and ease of maintenance make it a real cost saver. The ergonomic design and the integrated silencer make it the ideal tool for industrial applications and for the do it yourselfer.

Popular Applications

Upholstery, bedding, packaging, wicker work, speaker grills, automotive industry.



Technical Data

Model:	71/16-421 Standard	71/16-421 w/contact trip
Part number:	12000330	12000348
Loading type:	bottom loading	bottom loading
Fastener type:	71	71
Magazine capacity:	190	190
Standard load, strips x fasteners/strip:	1 x 182	1 x 182
Working pressure:	75-90 P.S.I.	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.	90 P.S.I.
Air consumption:	.01 cu. ft./cycle @ 90 P.S.I.	.01 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"	ø 3/8"
Weight:	2.14 lbs.	2.14 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions, silencer.

The tool is also available with a thin nose: **71/16-421 Profile** (12000324).

Subject to technical modifications.

Accessories

Part number	Description
14403330	Remote firing valve assembly
14406175	Special back nose assembly for 1 1/4" staples and shorter only

All BeA pneumatic tools can be jig mounted.
We supply the necessary accessories.



This tool conforms to the EC Directive
for Machinery (89/392 EWG)


Pneumatic Tacker

71/16-421



BeA Fasteners U.S.A.
 2100-120 Fairfax Road
 Greensboro, NC 27407
 Phone: (336) 510-4232
 Fax: (336) 510-4233

Fastener type 71



Description	L = Length in.
71/04 NK	5/32"
71/05 NK	3/16"
71/06 NK	1/4"
71/08 NK	5/16"
71/10 NK	3/8"
71/12 NK	1/2"
71/14NK	9/16"
71/16 NK	5/8"

Other lengths and finishes are also available on request.

Fastener nomenclature:

NK = Galvanized steel
 NKS = Galvanized steel, high carbon
 BK = Brite steel
 BKS = Brite steel, high carbon

HZ = Resin coated
 NR = Stainless steel
 DP = Divergent point